

SAFE JOB PROCEDURE

October 27, 2009

PURPOSE/APPLICATION

<u> PPE</u>

- Safety boots
- Hard hat
- Hearing protection
- Eye protection
- Gloves

TRAINING

- Orientation
- Competency

TOOLS/EQUIPMENT

| # | Job Steps | Hazards | Control Measures |
|---|--------------------|---|---|
| 1 | Pre-startup | Slips, trips, falls | Do a circle check |
| 2 | Startup | Mechanical failureEnvironmental incident | use 3-point contact when mounting or dismounting forklift |
| | | | ensure cab is clean and windows are clear |
| | | | check gauges after starting and let warm up |
| | | | walk around machine, check lights and fluid leaks |
| | | | operate controls, ensure hydraulic pressure |
| | | | test brakes, horn and back up alarm |
| 3 | Operating forklift | Equipment trafficPedestrian traffic | maintain safe speed at all times |
| | | Uneven ground | carry loads as low as possible |
| | | Suspended loads | be aware of other yard equipment and workers |
| | | Unbalanced loads | approach green chain area with caution |
| | | | ensure workers are clear when lifting load |
| | | | ensure forks are positioned correctly for load |
| | | | use proper ergonomics when positioning forks |

FORKLIFT OPERATOR



SAFE JOB PROCEDURE

October 27, 2009

FORKLIFT OPERATOR

| # | Job Steps | Hazards | Control Measures | | |
|---|----------------|--------------------------------------|--|--|--|
| | | | never walk under raised load | | |
| | | | packages, maximum 3 high | | |
| | | | keep packages neat and straight | | |
| | | | avoid side hill travel | | |
| | | | clean up any lost logs ASAP | | |
| 4 | Loading trucks | Miscommunication | communicate will truck driver, | | |
| | | Property Damage | make a plan before you start | | |
| 5 | Fueling | Environmental incident | park safe distance from tank | | |
| | | | no smoking | | |
| | | | attend fuel nozzle until full, store hose and nozzle in proper place | | |
| 6 | Shutdown | Tripping hazard | park on level ground | | |
| | | Pinch points | lower forks | | |
| | | | apply park brake | | |
| | | | shut off key and master switch | | |
| | | | use 3-point contact to dismount | | |
| | | | report any problems to mechanic | | |

Additional Precautions:

Training

- The employee shall issue a certificate to a worker who operates a lift truck once that worker has been trained and tested.
- Only workers who have been trained and issued a certificate will be allowed to operate a power lift truck.
- Certificates will be issued to the worker once the worker has demonstrated competency in the power lift truck operation.
- The employer will maintain records of the training the worker receives.
- Power lift trucks must be clearly marked with a visible load rating chart.

SJP-23



SAFE JOB PROCEDURE

October 27, 2009

SJP-23 FORKLIFT OPERATOR

REFERENCE/REGULATIONS

| Developed by: | 1. | Marty Fulkerth | 2. | Date: | Oct 27/09 |
|---------------|----|----------------|----|-----------|-----------|
| | 3. | | 4. | - | |
| Revised by: | 1. | Jay Pilon | 2. | Date: | Apr 19/10 |