STRIKE	RIGGING EQUIPMENT INSPECTION	CF-S-14

All rigging equipment, including wire rope, slings, shackles, etc., is to be inspected prior to use to ensure that the rigging is in good condition, functional, and safe. Any defective rigging identified must be tagged, removed from service, and reported to the Supervisor. All lifting components require completion and proof of Periodic Inspection at least annually (some monthly-quarterly depending on service requirements), as well as verification of any OEM requirements of the equipment prior to use. Refer to SWP 54 – Rigging or speak to your local HSE representative for further guidance on rigging and inspection guidance.

Type of Rigging Equipment (Synthetic Sling, Wire Rope, Shackle, etc.)	Serial # / ID (ID acceptable for internal tracking document)	Next Periodic Inspection Date	Tag Legible (serial number/lifting ratings)	Burns / Melting / Charring / Chemical Stains / Corrosion	Broken Stitches / Wires	Cuts / Tears / Holes	Bird-caging / Kinking / Doglegs	Damaged / Broke / Bent / Malformed Hardware	Fit For Service	Initial
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	
			☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	☐ Yes ☐ No	

Date: _____ Approved/Reviewed By: _____ Signature: _____